

CDXconventional Intrinsically Safe

IFD-E(Exd)

Explosion-Proof IR³ Infra-Red Flame Detector

Features

- ▶ Unaffected by convection currents, draughts or wind and solar-blind
- ▶ Tolerant of fumes, vapours, dust and mist
- ▶ ATEX certified to II 2GD Ex d IIC T4 Gb Ex tb IIIC T135°C Db IP66 A21 (Zones 1, 21, 2 and 22)
- ▶ Responsive to a flame more than 25 m away
- ▶ Selectable response speed
- ▶ Class 1 performance as defined in BS EN54-10:2002 (on the high sensitivity setting)
- ▶ Optical self-test
- ▶ SIL2 Capable
- ▶ Worldwide approvals include EN54:10, with VdS and LPCB certification.



Description

Model IFD-E(EXD) is an Explosion-Proof IR³ flame detector designed for use where open flaming fires may be expected and responds to the light emitted from flames during combustion.

The detector discriminates between flames and other light sources by responding

only to particular optical wavelengths and flame flicker frequencies. This enables the detector to avoid false alarms due to such factors as flickering sunlight. Ideal for the detection of flames from the burning of Aviation Fuels (kerosene), Butane, Grain & Feeds, Hydrogen, Paper, Natural Gas, Petrol (gasoline) etc.

Specification

Ordering Codes	IFD-E(EXD) IFD-MB (Stainless Steel Mounting Bracket)	
Operating Voltage	14 ~ 30 VDC	
Alarm Current (selected via by DIL switches)	9 ~ 28 mA	
Test Signal Voltage	14 to 30 VDC	
Relay Contact Ratings	Current	1.0 A (max)
	Voltage	50 VDC (max)
	Power	30 W (max) (resistive loads only)
Power Up Time	2 seconds (max)	
Field of View	90° min. Cone	
Range	Class 1 - 0.1m ² n-heptane at 25m	
	Class 3 - 0.1m ² n-heptane at 12m	
Operating Wavelength Band	IR (0.75 ~ 2.7 μm)	
Operating Temperature Range	- 10 °C to + 55 °C (sensor limit - 10 °C to + 40 °C (T4))	
Storage Temperature Range	- 20 °C to + 65 °C	
Maximum Humidity	95% RH - Non Condensing	
Ingress Protection Rating	IP66	
Colour / Case Material	Red / Copper Free Aluminium Alloy LM25	
Weight (kg) / Dimensions (mm)	2.5 / H 150 x W 146 x D 137	